

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT

Product code : 6058.

1.2. Relevant identified uses of the substance or mixture and uses advised against

SHOE DEODORIZER DISINFECTANT

TP2: Disinfectants for surfaces, materials, equipment and furniture without direct contact with food or feed

1.3. Details of the supplier of the safety data sheet

Registered company name : HYDRACHIM.

Address : Z.A. Route de Saint Poix.35370.LE PERTRE.FRANCE.

Telephone : +33 (0)2.99.96.80.08. Fax : +33 (0)2.99.96.82.00.

reglementation@hydrachim.fr

www.hydrachim.fr

FABRICANT

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

2.2. Label elements

Biocidal detergent mixture (see section 15).

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07

Signal Word :

WARNING

Hazard statements :

H226

Flammable liquid and vapour.

H319

Causes serious eye irritation.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P103

Read carefully and follow all instructions.

Precautionary statements - Prevention :

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233

Keep container tightly closed.

P240

Ground and bond container and receiving equipment.

P241

Use explosion-proof electrical/ventilating/lighting/.../equipment.

P242

Use non-sparking tools.

P243

Take action to prevent static discharges.

P273

Avoid release to the environment.

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058

P280	Wear protective gloves, protective clothing, eye protection and face protection.
Precautionary statements - Response :	
P303 + P361 + P353	IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin (or hair) with water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use CO ₂ powder with extinction or pulverized water for extinction.
Precautionary statements - Storage :	
P403 + P235	Store in a well-ventilated place. Keep cool.
Precautionary statements - Disposal :	
P501	Dispose of contents and container to approved waste disposal facility in accordance with national regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: 603_002_00_5 CAS: 64-17-5 EC: 200-578-6 REACH: 01-2119457610-43-XXXX	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319	[1]	10 <= x % < 25
ETHANOL INDEX: 0091 CAS: 68424-85-1 EC: 270-325-2 REACH: 01-2119965180-41-XXXX	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400		0 <= x % < 1
QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES	M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 1		
INDEX: 612_131_00_6 CAS: 7173-51-5 EC: 230-525-2	GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H301 Skin Corr. 1B, H314 Aquatic Acute 1, H400		0 <= x % < 1
DIDECYLDIMETHYLAMMONIUM CHLORIDE	M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 1		

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In case of impaired consciousness place in recovery position and seek medical advice immediately.

Keep the container or label available.

In the event of exposure by inhalation :

Remove the victim away from the product. Provide fresh air. Consult a doctor in case the symptoms persist.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058

In the event of splashes or contact with skin :

If an irritation appears or if the contamination is spread or prolonged, to consult a doctor.

Remove contaminated clothing, wash affected skin immediately with plenty of water for 10 to 15 minutes.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically non-conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

Keep the bowl closed well in a freshly well ventilated place.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

Suitable packaging materials :

- Compatible grades HDPE.

7.3. Specific end use(s)

The mixture is a biocidal product. It must not be used for applications other than those described in this safety data sheet and in the technical documents concerning the product.

Product intended for strictly professional use.

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5		1000 ppm		A3	

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes
64-17-5		200 ppm 380 mg/m ³		4(1 TM 1 TM)

- France (INRS - ED984 / 2019-1487) :

CAS	VME-ppm :	VME-mg/m ³ :	VLE-ppm :	VLE-mg/m ³ :	Notes :	TMP No :
64-17-5	1000	1900	5000	9500	-	84

- Switzerland (SUVAPRO 2017) :

CAS	VME	VLE	Valeur plafond	Notations
64-17-5	500 ppm 960 mg/m ³	1000 ppm 1920 mg/m ³		SSC

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
64-17-5	1000 ppm 1920 mg/m ³	- ppm - mg/m ³			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES (CAS: 68424-85-1)

Final use:Exposure method:
Potential health effects:
DNEL :**Workers.**Dermal contact.
Long term systemic effects.
5.7 mg/kg body weight/dayExposure method:
Potential health effects:
DNEL :Inhalation.
Long term systemic effects.
3.96 mg of substance/m³**Final use:**Exposure method:
Potential health effects:
DNEL :**Consumers.**Dermal contact.
Long term systemic effects.
3.4 mg/kg body weight/dayExposure method:
Potential health effects:
DNEL :Inhalation.
Long term systemic effects.
1.64 mg of substance/m³

ETHANOL (CAS: 64-17-5)

Final use:Exposure method:
Potential health effects:
DNEL :**Workers.**Dermal contact.
Long term systemic effects.
343 mg/kg body weight/dayExposure method:
Potential health effects:
DNEL :Inhalation.
Short term local effects.
1900 mg of substance/m³Exposure method:
Potential health effects:
DNEL :Inhalation.
Long term systemic effects.
950 mg of substance/m³

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058**Final use:**Exposure method:
Potential health effects:
DNEL :**Consumers.**Ingestion.
Long term systemic effects.
87 mg/kg body weight/dayExposure method:
Potential health effects:
DNEL :Dermal contact.
Long term systemic effects.
206 mg/kg body weight/dayExposure method:
Potential health effects:
DNEL :Inhalation.
Short term local effects.
950 mg of substance/m³Exposure method:
Potential health effects:
DNEL :Inhalation.
Long term systemic effects.
114 mg of substance/m³**Predicted no effect concentration (PNEC):****QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES (CAS: 68424-85-1)**Environmental compartment:
PNEC :Soil.
7 mg/kgEnvironmental compartment:
PNEC :Fresh water.
0.0009 mg/lEnvironmental compartment:
PNEC :Sea water.
0.00009 mg/lEnvironmental compartment:
PNEC :Intermittent waste water.
0.00016 mg/lEnvironmental compartment:
PNEC :Fresh water sediment.
0.267 mg/kgEnvironmental compartment:
PNEC :Marine sediment.
0.0267 mg/kgEnvironmental compartment:
PNEC :Waste water treatment plant.
0.4 mg/l**ETHANOL (CAS: 64-17-5)**Environmental compartment:
PNEC :Soil.
0.63 mg/kgEnvironmental compartment:
PNEC :Fresh water.
0.96 mg/lEnvironmental compartment:
PNEC :Sea water.
0.79 mg/lEnvironmental compartment:
PNEC :Intermittent waste water.
2.75 mg/lEnvironmental compartment:
PNEC :Fresh water sediment.
3.6 mg/kgEnvironmental compartment:
PNEC :Marine sediment.
2.9 mg/kg

Environmental compartment:

Waste water treatment plant.

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058

PNEC : 580 mg/l

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVC (polyvinyl chloride)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A2 (Brown)

Use the product in ventilated aera

In normal use, a breathing protection is not required.

Use the respiratory protection on high exposure levels for example during the crossing of the limit value at the workplace

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****General information :**

Physical state : Fluid liquid.

Aspect : Clear green

Important health, safety and environmental information

pH : 7.00 +/- 0.50.

Neutral.

Boiling point/boiling range : Not relevant.

Flash Point : 34.50 °C.

Method for determining the flash point:

ISO 13736 (Determination of flash point - Abel closed-cup method).

Vapour pressure (50°C) : Not relevant.

Density : = 0.96 g/cm3 +/- 0.01

Water solubility : Soluble.

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058

Melting point/melting range : Not relevant.
Self-ignition temperature : Not relevant.
Decomposition point/decomposition range : Not relevant.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces
- frost

10.5. Incompatible materials

Keep away from :

- oxidising agents

Do not mix with other disinfectants.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

Acute toxicity :

DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS: 7173-51-5)

Oral route : LD50 = 238 mg/kg
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 = 3342 mg/kg
Species : Rabbit

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES (CAS: 68424-85-1)

Oral route : LD50 = 795 mg/kg
Species : Rat

ETHANOL (CAS: 64-17-5)

Oral route : LD50 = 10470 mg/kg
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 20000 mg/kg

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058

Species : Rabbit

Inhalation route (Vapours) : LC50 = 117-125 mg/l
Species : Rat
OECD Guideline 403 (Acute Inhalation Toxicity)
Duration of exposure : 4 h

Skin corrosion/skin irritation :

DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS: 7173-51-5)
Corrosivity : Causes severe skin burns.
Species : Rabbit
OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Effect observed : Overall irritation score
Species : Rabbit

Respiratory or skin sensitisation :

DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS: 7173-51-5)
Buehler Test : Non-sensitiser.
Species : Guinea pig
Other guideline

Germ cell mutagenicity :

DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS: 7173-51-5)
Mutagenesis (in vivo) : Negative.
Species : Rat
OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)

OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Ames test (in vitro) : Negative.

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES (CAS: 68424-85-1)
No mutagenic effect.

Mutagenesis (in vitro) : Negative.

Ames test (in vitro) : Negative.

Carcinogenicity :

DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS: 7173-51-5)
Carcinogenicity Test : Negative.
No carcinogenic effect.

11.1.2. Mixture

Serious damage to eyes/eye irritation :

Causes severe eye irritation (H319).

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 91-64-5 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 67-63-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 64-17-5 : IARC Group 1 : The agent is carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS: 7173-51-5)

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058

Fish toxicity :	LC50 = 0.19 mg/l Factor M = 1 Species : Pimephales promelas Duration of exposure : 96 h NOEC = 0.032 mg/l Species : Danio rerio Duration of exposure : 35 days OECD Guideline 210 (Fish, Early-Life Stage Toxicity Test)
Crustacean toxicity :	EC50 = 0.062 mg/l Factor M = 10 Species : Daphnia magna Duration of exposure : 48 h NOEC = 0.010 mg/l Factor M = 1 Species : Daphnia magna Duration of exposure : 21 days OECD Guideline 211 (Daphnia magna Reproduction Test)
Algae toxicity :	ECr50 = 0.026 mg/l Factor M = 10 Species : Pseudokirchnerella subcapitata Duration of exposure : 96 h OECD Guideline 201 (Alga, Growth Inhibition Test)
ETHANOL (CAS: 64-17-5) Fish toxicity :	LC50 = 11200 mg/l Duration of exposure : 96 h NOEC = 250 mg/l OECD Guideline 212 (Fish, Short-term Toxicity Test on Embryo and Sac-Fry Stages)
Crustacean toxicity :	EC50 > 857 mg/l Duration of exposure : 48 h NOEC > 9.6 mg/l
Algae toxicity :	ECr50 > 275 mg/l Duration of exposure : 72 h
QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES (CAS: 68424-85-1) Fish toxicity :	LC50 = 1 mg/l Factor M = 1 Duration of exposure : 96 h
Crustacean toxicity :	EC50 = 0.1 mg/l Factor M = 10 Species : Daphnia magna Duration of exposure : 48 h
Algae toxicity :	ECr50 = 0.1 mg/l Factor M = 10 Species : Pseudokirchnerella subcapitata Duration of exposure : 72 h NOEC = 0.01 mg/l Factor M = 1 Species : Pseudokirchnerella subcapitata

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058

OECD Guideline 201 (Alga, Growth Inhibition Test)

12.1.2. Mixtures

Harmful to aquatic life with long lasting effects (H412).

12.2. Persistence and degradability

12.2.1. Substances

DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS: 7173-51-5)

Biodegradability : Rapidly degradable.

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES (CAS: 68424-85-1)

Biodegradability : Rapidly degradable.

ETHANOL (CAS: 64-17-5)

Chemical oxygen demand : DCO = 1.99 g/g

Biodegradability : Rapidly degradable.

12.2.2. Mixtures

no degradability data is available, the substance is considered as not degrading quickly.

Biodegradability :

Surfactant(s) contained in this preparation complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be at their direct request or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

12.3.1. Substances

DIDECYLDIMETHYLAMMONIUM CHLORIDE (CAS: 7173-51-5)

Bioaccumulation : BCF = 81

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES (CAS: 68424-85-1)

Octanol/water partition coefficient : log K_{ow} < 3.

ETHANOL (CAS: 64-17-5)

Octanol/water partition coefficient : log K_{ow} = -0.3

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

07 06 04 * other organic solvents, washing liquids and mother liquors

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2020).

14.1. UN number

1993

14.2. UN proper shipping nameUN1993=FLAMMABLE LIQUID, N.O.S.
(ethanol)**14.3. Transport hazard class(es)**

- Classification :



3

14.4. Packing group

III

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	30	5 L	274 601	E1	3	D/E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	3	-	III	5 L	F-E, S-E	223 274 955	E1	Category A	-

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	III	355	60 L	366	220 L	A3	E1
	3	-	III	Y344	10 L	-	-	A3	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)

- Container information:

No data available.

- Particular provisions :

No data available.

- Labelling for detergents (EC Regulation No. 648/2004,907/2006) :

- less than 5 % : nonionic surfactants

- disinfectants

- perfumes

- allergenic fragrances :

coumarin

- Labelling for biocidal products (Regulation 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC)

:

Name	CAS	%	Product-type
DIDECYLDIMETHYLAMMONIUM CHLORIDE	7173-51-5	2.70 g/l	02

WINTERSTEIGER AG - STERIBIO PIN/MENTHE VERT - 6058

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-16-ALKYLDIMETHYL, CHLORIDES	68424-85-1	4.83 g/l	02
ETHANOL	64-17-5	231.6 g/l	02

Product-type 2 : Disinfectants and algacides not intended for direct application to humans or animals.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.