

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : HARDENER HW 2951

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Hardener

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone

Emergency telephone : Berlin: 0049 30 19 24 0 & 0049 30 30 68 6 7 11
Bonn: 0049 228 19 27 0 & 0049 228 28 7 3 32 11
Erfurt: 0049 361 73 07 30
Freiburg: 0049 761 16 24 0
Göttingen: 0049 51 19 24 0 & 0049 551 38 31 80
Homburg: 0049 6841 19 24 0
Mainz: 0049 6131 19 24 0 & 0049 6131 23 24 66
München: 0049 89 19 24 0
Nürnberg: 0049 911 39 8 2 45 1
EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Category 1C

H314: Causes severe skin burns and eye damage.

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Chronic aquatic toxicity, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P273 Avoid release to the environment.
Response:
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients which must be listed on the label:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine

2,4,6-tris(dimethylaminomethyl)phenol

3-aminopropyltriethoxysilane

2.3 Other hazards

None known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version 1.2 Revision Date: 22.10.2015 SDS Number: 400001007752 Date of last issue: 15.07.2015
Date of first issue: 19.05.2015

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

Chemical Name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	10563-29-8 234-148-4 -	Acute Tox. 4; H302 Skin Corr. 1A; H314 Skin Sens. 1B; H317	>= 3 - <= 7
2,2'-[1,2-Ethanediy]bis(oxy)]bis(ethanethiol)	14970-87-7 239-044-2 -	Acute Tox. 4; H332, H302 Aquatic Chronic 2; H411	>= 3 - <= 7
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2 202-013-9 01-2119560597-27	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412 Skin Sens. 1B; H317	>= 1 - <= 3
3-Aminopropyltriethoxysilane	919-30-2 213-048-4 -	Acute Tox. 4; H302 Skin Corr. 1B; H314 Skin Sens. 1B; H317	>= 0,1 - <= 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Seek medical advice.
- If swallowed : Rinse mouth with water.
Do NOT induce vomiting.
Consult a physician if necessary.

4.2 Most important symptoms and effects, both acute and delayed

None known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No data is available on the product itself.

5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Do not allow contact with soil, surface or ground water.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

None

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat, drink or smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep containers tightly closed in a cool, well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses
- Hand protection
- Material : butyl-rubber
- Break through time : > 8 h
Nitrile rubber
10 - 480 min
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
- Skin and body protection : Protective suit
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Combined particulates and organic vapor type

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: paste
Color	: gray
Odor	: amine-like
pH	: 10, Concentration: 500 g/l (20 °C) Method: Measured
Boiling point	: > 100 °C
Flash point	: 125 °C Method: Pensky-Martens closed cup, closed cup
Vapor pressure	: < 0,95 hPa (20 °C)
Density	: 1,9 g/cm ³ (25 °C)
Solubility(ies) Water solubility	: practically insoluble (20 °C)
Viscosity Viscosity, dynamic	: thixotropic

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under normal conditions.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases
Strong oxidizing agents

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

10.6 Hazardous decomposition products

Burning produces obnoxious and toxic fumes.
Carbon oxides
Nitrogen oxides (NO_x)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Acute oral toxicity : LD50 (Rat, male and female): 1.669 mg/kg
Method: OECD Test Guideline 401

2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol):

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after single ingestion.

3-aminopropyltriethoxysilane:

Acute oral toxicity : LD50 (Rat, male and female): 1.491 - 2.688 mg/kg
Method: Acute Oral Toxicity

Ingredients:

2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol):

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

3-aminopropyltriethoxysilane:

Acute inhalation toxicity : LC50 (Rat, male): > 5 ppm
Exposure time: 6 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Acute dermal toxicity : LD50 (Rabbit): 1.310 mg/kg

3-aminopropyltriethoxysilane:

Acute dermal toxicity : LD50 (Rabbit, male and female): 4.075 mg/kg
Method: Acute Dermal Toxicity
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

Skin corrosion/irritation

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:
Species: Rabbit
Assessment: Corrosive
Method: OECD Test Guideline 404
Result: Corrosive

2,4,6-tris(dimethylaminomethyl)phenol:
Species: Rabbit
Method: OECD Test Guideline 404
Result: Corrosive after 1 to 4 hours of exposure

3-aminopropyltriethoxysilane:
Species: Rabbit
Method: OECD Test Guideline 404
Result: Causes burns.

Serious eye damage/eye irritation

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:
Assessment: Severe eye irritation
Result: Corrosive

2,4,6-tris(dimethylaminomethyl)phenol:
Species: Rabbit
Assessment: Corrosive
Result: Irreversible effects on the eye

3-aminopropyltriethoxysilane:
Species: Rabbit
Method: OECD Test Guideline 405
Result: Risk of serious damage to eyes.

Respiratory or skin sensitization

Ingredients:

1,3-Propanediamine, N3-(3-aminopropyl)-N1,N1-dimethyl-:
Routes of exposure: Skin
Species: Guinea pig
Method: OECD Test Guideline 406
Result: The product is a skin sensitizer, sub-category 1B.

2,4,6-tris(dimethylaminomethyl)phenol:
Routes of exposure: Skin
Species: Guinea pig
Method: OECD Test Guideline 406
Result: negative

Assessment: The product is a skin sensitizer, sub-category 1B.
Result: The product is a skin sensitizer, sub-category 1B.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

3-aminopropyltriethoxysilane:

Routes of exposure: Skin

Species: Guinea pig

Method: OECD Test Guideline 406

Result: The product is a skin sensitizer, sub-category 1B.

Assessment: No data available

Germ cell mutagenicity

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 487
Result: negative

: Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

: Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

2,4,6-tris(dimethylaminomethyl)phenol:

Genotoxicity in vitro : Concentration: 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

: Concentration: 2500 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

: Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Ingredients:

3-aminopropyltriethoxysilane:

Genotoxicity in vivo : Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

Carcinogenicity

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Species: Mouse, (male)

Application Route: Dermal

Exposure time: 20 month(s)

Frequency of Treatment: 3 daily

Result: negative

Carcinogenicity - Assessment : No data available

Reproductive toxicity

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Effects on fertility : Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 422

2,4,6-tris(dimethylaminomethyl)phenol:

Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 422

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Effects on fetal development : Species: Rat, male and female

Application Route: Oral

General Toxicity Maternal: NOAEL (No observed adverse effect level): 15 mg/kg body weight

Developmental Toxicity: NOAEL (No observed adverse effect level): 15 mg/kg body weight

Embryo-fetal toxicity.: NOAEL (No observed adverse effect level): 15 mg/kg body weight

Method: OECD Test Guideline 422

Result: No effects on fertility and early embryonic development were detected.

GLP: yes

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

STOT-single exposure

No data available

STOT-repeated exposure

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

Repeated dose toxicity

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Species: Rat, male and female

NOEC: 550

Application Route: Ingestion

Test atmosphere: vapor

Exposure time: 3 Weeks Number of exposures: 7 d

Method: Subchronic toxicity

Species: Mouse, male

NOAEL (No observed adverse effect level): $\geq 56,3$

Application Route: Skin contact

Exposure time: 20 h Number of exposures: 3 d

Method: Chronic toxicity

2,4,6-tris(dimethylaminomethyl)phenol:

Species: Rat, male and female

No-observed-effect level: 15 mg/kg

Application Route: Ingestion

Exposure time: 1.032 h Number of exposures: 7 d

Method: Subacute toxicity

3-aminopropyltriethoxysilane:

Species: Rat, male and female

NOAEL (No observed adverse effect level): 200 mg/kg

Application Route: Ingestion

Exposure time: 2.160 h Method: Subchronic toxicity

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 9,2 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 21 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Toxicity to bacteria : EC50 (Pseudomonas putida): 181 mg/l
Exposure time: 16 h
Test Type: static test
Test substance: Fresh water
Method: DIN 38 412 Part 8

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol):

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 175 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

- Toxicity to daphnia and other aquatic invertebrates : LC50 : 718 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Marine water
- Toxicity to algae : ErC50 (Desmodesmus subspicatus (Scenedesmus subspicatus)): 84 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201
- Ecotoxicology Assessment
Chronic aquatic toxicity : This product has no known ecotoxicological effects.
- 3-aminopropyltriethoxysilane:
Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 934 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 331 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Desmodesmus subspicatus (Scenedesmus subspicatus)): > 1.000 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.3.
- Toxicity to bacteria : EC50 (Pseudomonas putida): 43 mg/l
Exposure time: 5,75 h
Test Type: static test
Test substance: Fresh water

12.2 Persistence and degradability

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 28 d
Method: ISO Method, other

2,4,6-tris(dimethylaminomethyl)phenol:

Biodegradability : Inoculum: activated sludge
Concentration: 2 mg/l
Result: Not readily biodegradable.
Biodegradation: 4 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

Exposure time: 28 d
Method: OECD Test Guideline 301D

3-aminopropyltriethoxysilane:

Biodegradability

: Inoculum: activated sludge
Concentration: 8,95 mg/l
Result: Not readily biodegradable.
Biodegradation: 67 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.A.

12.3 Bioaccumulative potential

Ingredients:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:

Partition coefficient: n-
octanol/water : log Pow: 0,5

log Pow: -0,56 (25 °C)
pH: 11,6
Method: OECD Test Guideline 107

2,4,6-tris(dimethylaminomethyl)phenol:

Partition coefficient: n-
octanol/water : log Pow: 0,219 (21,5 °C)
Method: OPPTS 830.7550

3-aminopropyltriethoxysilane:

Bioaccumulation

: Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 3,4
Remarks: Does not bioaccumulate.

Partition coefficient: n-
octanol/water

: log Pow: 1,7 (20 °C)
pH: 7

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Can be landfilled or incinerated, when in compliance with local regulations.
Where possible recycling is preferred to disposal or incineration.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

SECTION 14: Transport information

IATA

14.1 UN number : UN 2735
14.2 UN proper shipping name : Polyamines, liquid, corrosive, n.o.s.
(DIMETHYL DIPROPYL TRIAMINE, 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL)
14.3 Transport hazard class(es) : 8
14.4 Packing group : II
Labels : Corrosive
Packing instruction (cargo aircraft) : 855
Packing instruction (passenger aircraft) : 851

IMDG

14.1 UN number : UN 2735
14.2 UN proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(DIMETHYL DIPROPYL TRIAMINE, 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL)
14.3 Transport hazard class(es) : 8
14.4 Packing group : II
Labels : 8
EmS Code : F-A, S-B
14.5 Environmental hazards
Marine pollutant : no

ADR

14.1 UN number : UN 2735
14.2 UN proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(DIMETHYL DIPROPYL TRIAMINE, 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL)
14.3 Transport hazard class(es) : 8
14.4 Packing group : II
Labels : 8
14.5 Environmental hazards
Marine pollutant : no

RID

14.1 UN number : UN 2735
14.2 UN proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(DIMETHYL DIPROPYL TRIAMINE, 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL)
14.3 Transport hazard : 8

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

class(es)

14.4 Packing group : II

Labels : 8

14.5 Environmental hazards

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59) : Not applicable

EU Voluntary monitoring list for non-scheduled substances : Not applicable

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances
Not applicable

Water contaminating class (Germany) : WGK 2 water endangering

The ingredients of this product are reported in the following inventories:

CH INV : The mixture contains substances listed on the Swiss Inventory

TSCA : Not On TSCA Inventory

DSL : This product contains the following components that are not on the Canadian DSL nor NDSL.

AICS : Not in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : Low volume exemption

ISHL : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : Not in compliance with the inventory

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

IECSC : Low volume exemption

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

15.2 Chemical Safety Assessment

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H314 : Causes severe skin burns and eye damage.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H332 : Harmful if inhaled.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Chronic aquatic toxicity
Eye Dam. : Serious eye damage
Skin Corr. : Skin corrosion
Skin Sens. : Skin sensitization

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE. THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

HARDENER HW 2951

Version	Revision Date:	SDS Number:	Date of last issue: 15.07.2015
1.2	22.10.2015	400001007752	Date of first issue: 19.05.2015

THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.

SAFETY DATA SHEET



ARALDITE® AW 2101

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : ARALDITE® AW 2101
Registration number : Not available.
Product code : 00053326
Product description : Not available.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Resin for adhesive systems

1.3 Details of the supplier of the safety data sheet

Supplier : Huntsman Advanced Materials (Europe)BVBA
Everslaan 45
3078 Everberg / Belgium
Tel.: +41 61 299 20 41
Fax: +41 61 299 20 40

e-mail address of person responsible for this SDS : Global_Product_EHS_AdMat@huntsman.com

E-mail address to request full REACH registration number upon EU member State Authority request :
REACH_Registration_Nr_AM@huntsman.com

1.4 Emergency telephone number

Supplier

Telephone number : EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315
Eye Dam. 1, H318
Skin Sens. 1, H317
Aquatic Chronic 2, H411

Ingredients of unknown toxicity :

Ingredients of unknown ecotoxicity :

ARALDITE AW 2101

2/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 2: Hazards identification

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Xi; R36/38
 R43
 N; R51/53

Human health hazards : Irritating to eyes and skin. May cause sensitisation by skin contact.

Environmental hazards : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Causes serious eye damage.
 Causes skin irritation.
 May cause an allergic skin reaction.
 Toxic to aquatic life with long lasting effects.

Precautionary statements

General : Not applicable.

Prevention : Wear protective gloves: > 8 hours (breakthrough time): Ethyl Vinyl Alcohol Laminate (EVAL), butyl rubber. Wear eye or face protection. Avoid release to the environment.

Response : IF IN EYES: Rinse cautiously with water for several minutes. Immediately call a POISON CENTER or physician.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : epoxy phenol novolac resin
 butanedioldiglycidyl ether

Supplemental label elements : Not applicable.

Supplemental label elements : Contains epoxy constituents. See information supplied by the manufacturer.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification : None known.

ARALDITE AW 2101

3/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
Phenol, polymer with formaldehyde, glycidyl ether	CAS: 28064-14-4 EC: Polymer	30-60	Xi; R36/38 R43 N; R51/53	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
1,4-Bis(2,3-epoxypropoxy)butane	CAS: 2425-79-8 EC: 219-371-7 RRN: 01-2119494060-45	7-13	Xn; R20/21/22 Xi; R41, R38 R43 R52/53 See Section 16 for the full text of the R-phrases declared above.	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

ARALDITE AW 2101

4/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 4: First aid measures

- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : May cause burns to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
 pain
 watering
 redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
 pain or irritation
 redness
 blistering may occur
- Ingestion** : Adverse symptoms may include the following:
 stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

ARALDITE AW 2101

5/17

Date of printing	: 30 October 2014	(M)SDS no.	: 00053326
Date of issue	: 30 October 2014	Version	: 4

SECTION 5: Firefighting measures

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
 carbon dioxide
 Carbon monoxide
 metal oxide/oxides

5.3 Advice for firefighters

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

ARALDITE AW 2101

6/17

Date of printing	: 30 October 2014	(M)SDS no.	: 00053326
Date of issue	: 30 October 2014	Version	: 4

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- 7.2 Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: 2 to 40°C (35.6 to 104°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

- Storage hazard class Huntsman Advanced Materials** : Storage class 10, Environmentally hazardous liquids

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482

ARALDITE AW 2101

7/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 8: Exposure controls/personal protection

(Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived effect levels

No DELs available.

Predicted effect concentrations

No PECs available.

8.2 Exposure controls

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Material of gloves for long term application (BTT>480min): : Ethyl Vinyl Alcohol Laminate (EVAL), butyl rubber

Material of gloves for short term/splash application (10min <BTT<480min): : neoprene, nitrile rubber

(BTT = Break Through Time)

Use gloves approved to relevant standards e.g. EN 374 (Europe), F739 (US). Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material and dexterity. Always seek advice from glove suppliers. Additional information can be found for instance at www.gisbau.de.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

ARALDITE AW 2101

8/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 8: Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. [Paste.]
Colour : White.
Odour : Slight
Odour threshold : Not available.
pH : Not available.
Melting point/freezing point : Not available.
Initial boiling point and boiling range : >200°C
Flash point : Closed cup: 175°C
Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Burning time : Not applicable.
Burning rate : Not applicable.
Upper/lower flammability or explosive limits : Not available.
Vapour pressure : <0.0002 kPa [room temperature]
Vapour density : Not available.
Relative density : Not available.
Solubility(ies)
Water solubility : practically insoluble

20 deg C

Partition coefficient: n-octanol/ water (LogK_{ow}) : Not available.

Auto-ignition temperature : >400°C
Decomposition temperature : Not available.
Viscosity : Dynamic: Not available.
 Kinematic: Not available.
 Kinematic (40°C): Not available.

Explosive properties : Not available.

Oxidising properties : Not available.

9.2 Other information

Density : 1.65 g/cm³ [25°C (77°F)]

ARALDITE AW 2101

9/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : No specific data.
- 10.5 Incompatible materials** : strong acids, strong bases, strong oxidising agents
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
 Decomposition products may include the following materials: Burning produces obnoxious and toxic fumes., Carbon oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Endpoint	Species	Result	Exposure
Phenol, polymer with formaldehyde, glycidyl ether	LC0 Inhalation Vapour	Rat - Male	0.00001 ppm	5 hours
	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-
1,4-Bis(2,3-epoxypropoxy) butane	LD50 Oral	Rat - Female	>2000 mg/kg	-
	LD50 Dermal	Rat - Male, Female	2150 mg/kg	-
	LD50 Oral	Rat - Male, Female	1163 mg/kg	-

Conclusion/Summary : No additional information.

Acute toxicity estimates

Route	ATE value
Oral	12792.9 mg/kg
Dermal	12099.9 mg/kg
Inhalation (dusts and mists)	16.5 mg/l

Irritation/Corrosion

Product/ingredient name	Test	Species	Route of exposure	Result
Phenol, polymer with formaldehyde, glycidyl ether	OECD 405 Acute Eye Irritation/ Corrosion	Rabbit	Eyes	Mild irritant
	OECD 404 Acute Dermal Irritation/ Corrosion	Rabbit	Skin	Mild irritant
1,4-Bis(2,3-epoxypropoxy) butane	OECD 404 Acute Dermal Irritation/ Corrosion	Rabbit	Skin	Non-irritant.
	OECD 405 Acute Eye Irritation/ Corrosion	Rabbit	Eyes	Severe irritant

Conclusion/Summary

Skin : 1,4-Bis(2,3-epoxypropoxy)butane Based on the human occupational exposure data, this substance is considered as irritating to skin.

ARALDITE AW 2101

10/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 11: Toxicological information

Eyes : 1,4-Bis(2,3-epoxypropoxy)butane Severely irritating to eyes.

Respiratory : No additional information.

Sensitiser

Product/ingredient name	Test	Route of exposure	Species	Result
Phenol, polymer with formaldehyde, glycidyl ether	OECD 429 Skin Sensitisation: Local Lymph Node Assay	skin	Mouse	Sensitising
1,4-Bis(2,3-epoxypropoxy)butane	OECD 406 Skin Sensitization	skin	Guinea pig	Sensitising

Conclusion/Summary

Skin : No additional information.

Respiratory : No additional information.

Mutagenicity

Product/ingredient name	Test	Result
Phenol, polymer with formaldehyde, glycidyl ether	-	Positive
	-	Positive
	-	Negative
	-	Negative
1,4-Bis(2,3-epoxypropoxy)butane	OECD 471 Bacterial Reverse Mutation Test	Positive
	OECD 473 In vitro Mammalian Chromosomal Aberration Test	Positive
	OECD 474 Mammalian Erythrocyte Micronucleus Test	Negative

Conclusion/Summary : Phenol, polymer with formaldehyde, glycidyl ether The weight of the scientific evidence indicates that this material is non-genotoxic.

Carcinogenicity

Product/ingredient name	Test	Species	Exposure	Result	Route of exposure	Target organs
Phenol, polymer with formaldehyde, glycidyl ether	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Rat	2 years; 7 days per week	Negative	Oral	-
	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Rat	2 years; 5 days per week	Negative	Dermal	-
	OECD 453 Combined Chronic Toxicity/ Carcinogenicity Studies	Mouse	2 years; 3 days per week	Negative	Dermal	-

Conclusion/Summary : No additional information.

Reproductive toxicity

Product/ingredient name	Test	Species	Result/Result type	Target organs
Phenol, polymer with formaldehyde, glycidyl ether	OECD 416 Two-Generation Reproduction Toxicity Study	Rat	Oral: 540 mg/kg NOEL	-

Conclusion/Summary : No additional information.

ARALDITE AW 2101

11/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 11: Toxicological information

Teratogenicity

Product/ingredient name	Test	Species	Result/Result type
Phenol, polymer with formaldehyde, glycidyl ether	OECD 414 Prenatal Developmental Toxicity Study	Rat - Female	>540 mg/kg NOEL
	-	Rabbit - Female	>300 mg/kg NOEL
	OECD 414 Prenatal Developmental Toxicity Study	Rabbit - Female	180 mg/kg NOAEL

Conclusion/Summary : No additional information.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Inhalation** : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system.
- Ingestion** : May cause burns to mouth, throat and stomach.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Eye contact** : Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : No specific data.
- Ingestion** : Adverse symptoms may include the following:
stomach pains
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

ARALDITE AW 2101

12/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 11: Toxicological information

Product/ingredient name	Test	Result type	Result	Target organs
Phenol, polymer with formaldehyde, glycidyl ether 1,4-Bis(2,3-epoxypropoxy) butane	OECD 408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	NOAEL -	50 mg/kg	-
	OECD 411 Subchronic Dermal Toxicity: 90-day Study	NOEL	10 mg/kg	-
	OECD 411 Subchronic Dermal Toxicity: 90-day Study	NOAEL	100 mg/kg	-
	OECD 407 Repeated Dose 28-day Oral Toxicity Study in Rodents	NOAEL -	200 mg/kg	-

Conclusion/Summary : No additional information.
General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.
Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Test	Endpoint	Exposure	Species	Result
Phenol, polymer with formaldehyde, glycidyl ether	-	Acute EC50	72 hours Static	Algae	9.4 mg/l
	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute EC50	48 hours Static	Daphnia	1.7 mg/l
	-	Acute IC50	3 hours Static	Bacteria	>100 mg/l
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours Static	Fish	1.5 mg/l
	OECD 211 <i>Daphnia</i> Magna Reproduction Test	Chronic NOEC	21 days Semi-static	Daphnia	0.3 mg/l
1,4-Bis(2,3-epoxypropoxy) butane	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute EC50	24 hours Static	Daphnia	75 mg/l
	OECD 201 Alga, Growth Inhibition Test	Acute EL50	72 hours Static	Algae	>160 mg/l
	OECD 209 Activated Sludge, Respiration Inhibition Test	Acute IC50	3 hours Static	Bacteria	>100 mg/l
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours Static	Fish	24 mg/l

Conclusion/Summary : No additional information.

12.2 Persistence and degradability

Date of issue / Date of revision : 10/30/2014.

12/17

ARALDITE AW 2101

13/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 12: Ecological information

Product/ingredient name	Test	Period	Result
Phenol, polymer with formaldehyde, glycidyl ether 1,4-Bis(2,3-epoxypropoxy) butane	OECD Derived from OECD 301F (Biodegradation Test)	28 days	5 %
	OECD 301F Ready Biodegradability - Manometric Respirometry Test	28 days	43 %

Conclusion/Summary : No additional information.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Phenol, polymer with formaldehyde, glycidyl ether 1,4-Bis(2,3-epoxypropoxy) butane	Fresh water 4.83 days Fresh water 3.58 days Fresh water 7.1 days	-	Not readily
	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Phenol, polymer with formaldehyde, glycidyl ether 1,4-Bis(2,3-epoxypropoxy) butane	3.242	31	low
	-0.269	-	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

12.7 Other ecological information

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
07 02 08*	other still bottoms and reaction residues

Date of issue / Date of revision : 10/30/2014.

13/17

ARALDITE AW 2101

14/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 13: Disposal considerations


Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	14.1 UN number	14.2 UN proper shipping name
ADR/RID	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Epoxyphenol novolac resin)
IMDG	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Epoxyphenol novolac resin). Marine pollutant (Epoxy phenol novolac resin)
IATA	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Epoxyphenol novolac resin)


	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards	14.6 Special precautions for user	Additional information
ADR/RID	9 	III	Yes.	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	Hazard identification number 90 Special provisions 274 335 601 Tunnel code E
IMDG	9 	III	Yes.	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	Emergency schedules (EmS) F-A S-F

ARALDITE AW 2101

15/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 14: Transport information

IATA	9		III	Yes.	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	<u>Passenger and Cargo Aircraft</u> Quantity limitation: 450 L Packaging instructions: 964 <u>Cargo Aircraft Only</u> Quantity limitation: 450 L Packaging instructions: 964
------	---	---	-----	------	--	---

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

This product is compliant with the REACH Regulation EC 1907/2006.

Huntsman has pre-registered and is registering all of the substances that it manufactures in or imports into the European Economic Area (EEA) that are subject to Title II of the REACH Regulation.

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

Europe inventory : All components are listed or exempted.

Black List Chemicals : Not listed

Priority List Chemicals : Not listed

Integrated pollution prevention and control list (IPPC) - Air : Not listed

Integrated pollution prevention and control list (IPPC) - Water : Not listed

Integrated pollution prevention and control list (IPPC) - Air : Not listed

Integrated pollution prevention and control list (IPPC) - Water : Not listed

Integrated pollution prevention and control list (IPPC) - Air : Not listed

Integrated pollution prevention and control list (IPPC) - Water : Not listed

National regulations

ARALDITE AW 2101

16/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 15: Regulatory information

- References** : The provision of Safety Data Sheets comes under Regulation 6 of CHIP (CHIP is the recognised abbreviation for the Chemicals Hazard Information and Packaging Regulations). This is an addition to the Health and Safety at Work Act 1974.
- Australia inventory (AICS)** : All components are listed or exempted.
- Canada inventory** : Not determined.
- China inventory (IECSC)** : All components are listed or exempted.
- Japan inventory** : All components are listed or exempted.
- Korea inventory (KECI)** : All components are listed or exempted.
- New Zealand Inventory of Chemicals (NZIoC)** : All components are listed or exempted.
- Philippines inventory (PICCS)** : All components are listed or exempted.
- United States inventory (TSCA 8b)** : All components are listed or exempted.
- Chemical Weapons Convention List Schedule I Chemicals** : Not listed
- Chemical Weapons Convention List Schedule II Chemicals** : Not listed
- Chemical Weapons Convention List Schedule III Chemicals** : Not listed

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

📄 Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DNEL = Derived No Effect Level
 EUH statement = CLP-specific Hazard statement
 PNEC = Predicted No Effect Concentration
 RRN = REACH Registration Number

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements : H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

ARALDITE AW 2101

17/17

Date of printing : 30 October 2014 (M)SDS no. : 00053326
 Date of issue : 30 October 2014 Version : 4

SECTION 16: Other information

Full text of classifications [CLP/GHS] : Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4
 Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4
 Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4
 Aquatic Chronic 2, H411 LONG-TERM AQUATIC HAZARD - Category 2
 Aquatic Chronic 3, H412 LONG-TERM AQUATIC HAZARD - Category 3
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
 Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
 Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1

Full text of abbreviated R phrases : R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.
 R41- Risk of serious damage to eyes.
 R38- Irritating to skin.
 R36/38- Irritating to eyes and skin.
 R43- May cause sensitisation by skin contact.
 R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Full text of classifications [DSD/DPD] : Xn - Harmful
 Xi - Irritant
 N - Dangerous for the environment

(M)SDS no. : 00053326
 Date of printing : 10/30/2014.
 Date of issue/ Date of revision : 10/30/2014.
 Date of previous issue : 5/19/2014.
 Version : 4

Notice to reader

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

ARALDITE® is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more countries, but not all countries.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.